





COMPACT 45			
<i>Properties</i>	<i>Standard</i>	<i>Unit of measurement</i>	<i>Values</i>
DESCRIZIONE			
COMPACT 45	Prefabricated, prevarnished hevea solid wood parquet (22mm)		
Bottom layer	battes 15 mm, elastic foam made up of polyurethane 10mm		
Thickness	EN 13647	mm	47,0
Mass per unit area	-	Kg/m ²	18,2
CLASSIFICATION			
Multipurpose surfaces	EN 14904	Class	A4
Reaction to fire	EN 13501	Class	Cfl-s1
SPORT PROPERTIES			
Friction	EN 13036-4	-	81
Shock absorption	EN 14808	%	59
Vertical deformation	EN 14809	mm	2,3
Vertical ball behaviour	EN 12235	%	93
Specular gloss	EN 2813	%	43
TECHNICAL CHARACTERISTICS			
Rolling load	EN 1569	N	2800
Resistance to chemicals agents	EN 13442	-	5 no damages
Resistenza to abrasion	EN 14354	n° giri >1650	WR0
Resistenza to indentation	EN 1534	Brinell HB N/mm ²	32,8
Residual Indentation	EN 4712	mm	0,051
Resistance to chemicals agents	EN13442	class 5	compliant with the standard
Abrasion resistance	EN14354	>1000	compliant with the standard
Footprint resistance	EN4712	>0,001	compliant with the standard
Formaldehyde emission	EN14904	CLASS E1	compliant with the standard
Pentachlorophenol content	EN14904	<0,1%	compliant with the standard
OTHER			
Mark of conformity		CE Marking	
Certification bodies		Istituto Giordano	
Polizza RC prodotti		10 YEARS	
International federations		F I B A equipment & venue	