






<i>PLAYWOOD 4</i>			
<i>Properties</i>	<i>Standard</i>	<i>Unit of measurement</i>	<i>Values</i>
<b>DESCRIZIONE</b>			
PLAYWOOD S.14	Prefabricated, varnished parquet (14mm)		
Bottom layer	Elastic mattress made up of polyurethane granules warm pressed and mixed to an isocyanide glu (10 mm)		
Thickness	EN 13647	mm	33,00
Mass per unit area	-	Kg/m <sup>2</sup>	13,10
<b>CLASSIFICATION</b>			
Product specification	Professional system of wooden floor indoor multisport; category A4 according to the UNI-EN14904		
Thermal trenght	EN 12664	m <sup>2</sup> K/W	0,220
Reaction to fire	EN 13501	Class	Cfl-s1
Formaldehyde emissions	EN 717-2	-	No
Content of Pentachlorophenol	-	-	No
<b>SPORT PROPERTIES</b>			
Friction	EN 13036-4	-	82
Shock absorption	EN 14808	%	55
Vertical deformation	EN 14809	mm	2,6
Vertical ball behaviour	EN 12235	%	96
Specular gloss	EN 2813	%	19
<b>TECHNICAL CHARACTERISTICS</b>			
Rolling load	EN 1569	N	1500
Resistance to wear	-	g	0,060
Resistance to impact	-	-	0,04
<b>OTHER</b>			
Mark of conformity			CE Marking
Certification bodies			Istituto Giordano
International federations			F I B A equipment & venue